

PSEN op4B-4-090/1

630802












Safety light guard, Type 4, PL e, body protection, protected fieldheight 900 mm, muting function, supply voltage 24 V, connector M12, transmitter: 4-pin and 5-pin, receiver: 5-pin and 8-pin, connection cable not supplied with the device.

Technical details

Certifications:	CE;cULus Listed;TÜV
Number of beams:	4
Resolution of safety device:	315 mm
Height of protected field:	915 mm
Operating range (m):	0,5 - 50,0
Reaction time:	16.00 ms
Number of OSSD outputs:	2
Blanking:	Laser pointer
Cascading:	Finger
Supply voltage (V):	24,0
Supply voltage type:	DC
Protection type, housing:	IP65
Application in accordance with:	EN 61496-1;IEC 61496-2
Width dimension:	35.0 mm
Height dimension:	1053.0 mm
Depth dimension:	41.2 mm
Gross weight:	4200 g
Net weight:	3600 g
Ambient temperature:	-10 - 55 °C

Optional accessories

	630282	PSEN op cable M12 4-p. 0,75m L-Muting
	630295	PSEN op cableset
	630296	PSEN op cable axial M12 4-pole 30m
	630297	PSEN op cable axial M12 5-pole 30m
	630300	PSEN op cable axial M12 4-pole 3m
	630301	PSEN op cable axial M12 4-pole 5m
	630302	PSEN op cable axial M12 4-pole 10m
	630310	PSEN op cable axial M12 5-pole 3m
	630311	PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m



630313

PSEN op cable axial M12 8-p. shield. 3m



630314

PSEN op cable axial M12 8-p. shield. 5m



630315

PSEN op cable axial M12 8-p. shield. 10m



630326

PSEN op Bracket kit adjustable



630327

PSEN op Bracket kit antivibration



630328

PSEN op cable axial M12 8-p. shield. 30m



630340

Laser pointer for PSEN 4/2



630950

PSEN op Protective Column-060/1



630951

PSEN op Protective Column-090/1



630952

PSEN op Protective Column-120/1



630955

PSEN op Protective Base/1



630953

PSEN op Protective Column-165/1



630954

PSEN op Protective Column-190/1



630298

PSEN cable M12-5sf 20m



630362

PSEN op cable axial M12 4-pole 50m












630364

PSEN op cable axial M12 5-pole 50m



630368

PSEN op cable axial M12 8-p. shield. 50m

	630962	PSEN op Protective Column 3-080/1
	630961	PSEN op Protective Column 2-050/1
	630964	PSEN op Protective Column 4-120/1
	630963	PSEN op Protective Column 4-090/1
	630822	PSEN op2.3 L-Reflex
	630820	PSEN op2.1 L-Muting Set
	630821	PSEN op2.2 T-Muting Set
	630824	PSEN op muting bracket kit
	630823	PSEN op2.4 L-Reflector



630831

PSEN op3.1 Receiver NO/NC M12



630830

PSEN op3.3 Reflex NO/NC M12



630832

PSEN op3.2 Emitter M12
