

## PSEN sg2c-5LBKLC-M12/5 switch

570835



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Consisting of 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Key button for accessing & interlocking the safety gate; 3. Key switch (3 positions) 4. Illuminated pushbutton; 5. Blind cover M12/5 connection with enable switch.

### Dane

Certyfikacja:	CE;cULus Listed;TÜV;FCC
Zasada działania czujnika:	Transponder
Rodzaj kodowania:	Kodowany
Siła mocująca, kierunek kątowy:	2000 N
Liczba wyjść OSSD:	2
Liczba wejść:	2
Rodzaj przyłącza:	Federzugklemme steckbar
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania:	DC
Pobór mocy DC:	2.0 W
Numer przycisku:	2
Stopień ochrony obudowy:	IP54
Liczba elementów sterujących:	4
Szerokość:	46.5 mm
Wysokość:	568.0 mm
Głębokość:	74.5 mm
Ciężar brutto:	1290 g
Ciężar netto:	1200 g
Temperatura pracy:	-20 - 55 °C

## Akcesoria



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)



570890

PSEN sg2 actuator

## Akcesoria opcjonalne



401110

PIT en1.0p-5m-s



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin

---



570871

PSEN sg auxiliary release pin

---



570875

PSEN sg color covers (pushbutton)

---