

## PIT es Set3s-5c

400437



PITestop E-STOP/contact block set consisting of illuminated E-STOP pushbutton with E-STOP symbol and logo, and contact block with monitoring. 2 N/C, with spring-loaded terminals.

## Technical details

|                               |                             |
|-------------------------------|-----------------------------|
| Certifications:               | CE                          |
| Product standard:             | EN 60947-5-5;EN ISO 13850   |
| Release type:                 | Rotational                  |
| Actuator:                     | Pushbutton                  |
| Printing symbol:              | Pilz logo and E-STOP symbol |
| Colour button:                | Red                         |
| Protective collar:            | No                          |
| Self-monitored:               | Yes                         |
| Terminal type:                | Spring-loaded terminal      |
| Number of N/C:                | 2                           |
| Supply voltage (V):           | 12,0 - 30,0                 |
| Supply voltage type:          | AC/DC                       |
| Protection type, housing:     | IP65                        |
| Mounting type:                | Front panel installation    |
| Diameter of mounting cut-out: | 22.3 mm                     |
| Width dimension:              | 56.0 mm                     |
| Height dimension:             | 92.0 mm                     |
| Gross weight:                 | 88 g                        |
| Net weight:                   | 75 g                        |
| Ambient temperature:          | -25 - 55 °C                 |