

## PSEN ma1.3b-27/IX/VA/1switch

526243



Magnetic safety switch 2 n/o, 1 auxiliary contact n/o, cylindrical design M12, with 10 m cable, LED, IP67/69, operating distance depending on the actuator 8/12 mm, for applications with PSEN ix1, PU = 1 sensor without actuator, stainless steel housing, certification (CE, EAC, ECOLAB, TÜV, UL/cUL).

### Technical details

|                             |                                     |
|-----------------------------|-------------------------------------|
| Housing material:           | Stainless steel 1.4401              |
| Certifications:             | CE;EAC (Eurasian);TÜV;UL/cUL;ECOLAB |
| Sensor principle:           | magnetic                            |
| Number of N/O:              | 3                                   |
| Connection type:            | 10m Kabel                           |
| Switching voltage:          | 24 V                                |
| Type of switching voltage:  | DC                                  |
| Assured switching distance: | 8.0 mm                              |
| Assured release distance:   | 18.0 mm                             |
| Protection type, housing:   | IP67;IP69                           |
| Status indicator:           | With LED                            |
| Design:                     | Round                               |
| Width dimension:            | 12.0 mm                             |
| Height dimension:           | 12.0 mm                             |
| Depth dimension:            | 76.0 mm                             |
| Gross weight:               | 230 g                               |
| Net weight:                 | 220 g                               |
| Ambient temperature:        | -25 - 80 °C                         |
| Operating modes:            | Series connection                   |

## Accessories



535120

PSEN ix1 Interface for 4 PSEN 1

---