

PSEN ma1.4p-50/PSEN ma1.4-03mm/ 1unit

506332



Magnetic safety switch 2 n/o, 4-pin M8 male connector, square design, IP67, operating distance 3 mm, height design 18 mm, PU = 1 sensor with actuator.

## Technical details

Housing material:	PBT
Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	M8, 4pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	3.0 mm
Assured release distance:	12.0 mm
Protection type, housing:	IP65;IP67
Status indicator:	Without LED
Design:	square
Width dimension:	26.4 mm
Height dimension:	37.0 mm
Depth dimension:	18.0 mm
Gross weight:	67 g
Net weight:	51 g
Ambient temperature:	-10 - 55 °C
Operating modes:	Single connection

## Accessories



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m

## Optional accessories



380200

PSS67 Cable M8sf M12sm, 3m



380201

PSS67 Cable M8sf M12sm, 5m

380202

PSS67 Cable M8sf M12sm, 10m



380203

PSS67 Cable M8sf M12sm, 30m



380204

PSS67 Cable M8af M12sm, 3m



380205

PSS67 Cable M8af M12sm, 5m



380206

PSS67 Cable M8af M12sm, 10m



380207

PSS67 Cable M8af M12sm, 30m



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m

---



533120

PSEN Kabel Winkel/cable angleplug 5m

---



533121

PSEN Kabel Gerade/cable straightplug 5m

---



533130

PSEN Kabel Winkel/cable angleplug 10m

---



533131

PSEN Kabel Gerade/cable straightplug 10m

---



533140

PSEN Kabel Winkel/cable angleplug 30m

---



533141

PSEN Kabel Gerade/cable straightplug 30m

---



773600

PDP67 F 8DI ION

---