

PSEN op4H-SL-24-060/1

631123












Safety light guard, Type 4, PL e, hand protection (resolution 24 mm), protected field height 600 mm. Features: Cascading without dead zone, slimline design. Supply voltage 24 V, connector M12, transmitter: 5-pin, receiver 5-pin. Connection cable is not supplied with the device.

Technical details

Certifications:	CE;cULus Listed;TÜV
Product version:	1.0
Height of protected field:	600 mm
Number of beams:	32
Operating range (m):	0,2 - 6,0
Reaction time:	9.00 ms
Number of OSSD outputs:	2
Muting:	Fan
Supply voltage (V):	24,0
Supply voltage type:	DC
Protection type, housing:	IP65
Application in accordance with:	EN 61496-1;IEC 61496-2
Resolution of safety device:	24 mm
Width dimension:	15.4 mm
Height dimension:	600.0 mm
Depth dimension:	32.6 mm
Gross weight:	1450 g
Net weight:	750 g
Ambient temperature:	0 - 55 °C

Optional accessories

	630310	PSEN op cable axial M12 5-pole 3m
	630311	PSEN op cable axial M12 5-pole 5m
	630312	PSEN op cable axial M12 5-pole 10m
	630904	PSEN op Mirror-165/1
	630902	PSEN op Mirror-090/1
	630903	PSEN op Mirror-120/1
	630298	PSEN cable M12-5sf 20m
	631183	PSEN op SL cascading 0,1m
	631180	PSEN op SL Bracket C



631181

PSEN op SL Bracket L



631182

PSEN op SL Bracket O



631184

PSEN op SL cascading 0,5m



631185

PSEN op SL cascading 1m



631186

PSEN op SL Testpiece F 24 mm