

P2HZ X1P C 115VAC 3n/o 1n/c 2so

787435



Safety relay (standalone) Inputs: 1 N/O, 1 N/C per pushbutton Outputs: 3 N/O, 1 N/C, 2 semiconductor UB 115 V AC, width: 45 mm, plug-in spring-loaded terminals. Two-hand control device/monitoring the simultaneity of two-hand pushbuttons.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Two-hand monitoring Type III C
Standards:	EN 574 TYP III C;EN 62061;EN ISO 13849-1;VDE 0113-1
Operating modes:	Dual-channel;Detection of shorts across contacts
Number of instantaneous safety contacts:	3
Supply voltage (V):	115,0
Supply voltage type:	AC
Terminal style:	Plug-in
Terminal type:	Spring-loaded terminal
Stop category:	0
Max. current at DC13 I (6 cycles/min):	1.5 A
Width dimension:	45.0 mm
Height dimension:	101.0 mm
Depth dimension:	121.0 mm
Gross weight:	375 g
Net weight:	365 g
Ambient temperature:	-25 - 55 °C

Optional accessories



374291

PNOZ X Set spring loaded terminals P3+P4
