

PSEN op4F-s-14-120/1

630747



Safety light guard, Type 4, PL e, finger protection (resolution 14 mm), protected field height 1200 mm, supply voltage 24 V, connector M12, transmitter: 4-pin, receiver: 8-pin, connection cable not supplied with the device.

Technical details

| | |
|---------------------------------|------------------------------------|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV |
| Number of beams: | 128 |
| Resolution of safety device: | 14 mm |
| Resolution, protection type: | Reference marker |
| Height of protected field: | 1200 mm |
| Operating range (m): | 0,2 - 6,0 |
| Reaction time: | 36.00 ms |
| Number of OSSD outputs: | 2 |
| Muting: | Fan |
| Blanking: | Laser pointer |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Protection type, housing: | IP65 |
| Application in accordance with: | CLC/TS 61496-2;EN 61496-1 |
| Width dimension: | 32.3 mm |
| Height dimension: | 1283.2 mm |
| Depth dimension: | 36.9 mm |
| Gross weight: | 5960 g |
| Net weight: | 3960 g |
| Ambient temperature: | 0 - 55 °C |

Accessories



630303

PSEN op cable axial M12 4-p. shield. 3m



630304

PSEN op cable axial M12 4-p. shield. 5m



630305

PSEN op cable axial M12 4-p. shield. 10m



630306

PSEN op cable angle M12 4-p. shield. 3m



630307

PSEN op cable angle M12 4-p. shield. 5m



630308

PSEN op cable angle M12 4-p. shield. 10m



630309

PSEN op cable axial M12 4-p. shield. 30m



630313

PSEN op cable axial M12 8-p. shield. 3m



630314

PSEN op cable axial M12 8-p. shield. 5m



630315

PSEN op cable axial M12 8-p. shield. 10m



630316

PSEN op cable angle M12 8-p. shield. 3m



630317

PSEN op cable angle M12 8-p. shield. 5m



630318

PSEN op cable angle M12 8-p. shield. 10m



630319

PSEN op cable angle M12 4-p. shield. 30m



630328

PSEN op cable axial M12 8-p. shield. 30m



630329

PSEN op cable angle M12 8-p. shield. 30m
