

## PSEN sg2c-3LPE 2.2 unit

570880



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Coding: fully coded. 3 pushbuttons: 1. Illuminated pushbutton for activating the safety gate. 2. Pushbutton for accessing & interlocking the safety gate. 3. E-STOP Delivery scope: Sensing device with pushbuttons incl. colour caps and Escape release bar and actuator for right or left hinged gates.

## Dane

Certyfikacja:	CE;cULus Listed;TÜV;FCC
Zasada działania czujnika:	Transponder
Rodzaj kodowania:	Unikalny
Siła mocująca, kierunek kątowy:	2000 N
Liczba wyjść OSSD:	2
Liczba wejść:	2
Rodzaj przyłącza:	Federzugklemme steckbar
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania:	DC
Pobór mocy DC:	2.0 W
Numer przycisku:	2
Stopień ochrony obudowy:	IP54
Liczba elementów sterujących:	2
Szerokość:	200.0 mm
Wysokość:	465.0 mm
Głębokość:	108.0 mm
Ciężar brutto:	2950 g
Ciężar netto:	2570 g
Temperatura pracy:	-20 - 55 °C

## Akcesoria



570870

PSEN sg escape release pin



570871


PSEN sg auxiliary release pin

570875

PSEN sg color covers (pushbutton)



## Akcesoria opcjonalne



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin

570875

PSEN sg color covers (pushbutton)

