

## PSEN cs3.1a 1switch

541061



RFID safety switch 2 safe SC outputs, 5 m cable, one actuation direction, support for SDD, IP6K9K, switching distance depends on the actuator, PU = 1 piece coded switch without actuator.

### Technical details


|                             |   |
|-----------------------------|---|
| Certifications:             | CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC |
| Sensor principle:           | Transponder                               |
| Type of coding:             | Coded                                     |
| Number of OSSD outputs:     | 2   |
| Number of inputs:           | 2   |
| Connection type:            | 5m Kabel                                  |
| Supply voltage (V):         | 24,0                                      |
| Supply voltage type:        | DC  |
| Power consumption DC:       | 1.0 W                                     |
| Assured switching distance: | 8.0 mm                                    |
| Assured release distance:   | 20.0 mm                                   |
| Protection type, housing:   | IP6K9K                                    |
| Width dimension:            | 26.0 mm                                   |
| Height dimension:           | 37.0 mm                                   |
| Depth dimension:            | 18.0 mm                                   |
| Gross weight:               | 247 g                                     |
| Net weight:                 | 219 g                                     |
| Ambient temperature:        | -25 - 70 °C                               |

## Accessories



540080

PSEN cs1.1 1 actuator



541080

PSEN cs3.1 1 actuator



541087

PSEN cs3.1 low profile glue 1 actuator



541088

PSEN cs3.1 low profile screw 1 actuator

## Optional accessories



540334

PSEN/PDP67 M12-8sm screw terminals



540130

SDD ES ETH



540132

SDD ES PROFIBUS