

PSEN op4H-A-30-135/1

631027



Safety light guard, Type 4, PL e hand protection (resolution 30 mm), protected field height 1350 mm. Features: Muting, blanking, cascading, absence of dead zones. Programming is possible via Software PSENOptConfigurator or directly on the light guard. Supply voltage 24 V, connection via 18-pin pigtail cable on M12 connector. Connector M12 transmitter: 5-pin, receiver: Blanking 12-pin, muting 12-pin/5-pin. Pigtail cables are not supplied with the device.

Technical details

| | |
|---------------------------------|------------------------------------|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV |
| Number of beams: | 72 |
| Height of protected field: | 1350 mm |
| Operating range (m): | 0,2 - 20,0 |
| Reaction time: | 19.00 ms |
| Number of OSSD outputs: | 2 |
| Blanking: | Ventilation filter |
| Cascading: | Muting box |
| Supply voltage (V): | 24,0 |
| Supply voltage type: | DC |
| Application in accordance with: | EN 61496-1;IEC 61496-2 |
| Resolution of safety device: | 30 mm |
| Width dimension: | 35.0 mm |
| Height dimension: | 1356.3 mm |
| Depth dimension: | 40.8 mm |
| Gross weight: | 6350 g |
| Net weight: | 3300 g |
| Ambient temperature: | 0 - 50 °C |

Accessories



630297

PSEN op cable axial M12 5-pole 30m



630310

PSEN op cable axial M12 5-pole 3m



630311

PSEN op cable axial M12 5-pole 5m



630312

PSEN op cable axial M12 5-pole 10m



630298

PSEN cable M12-5sf 20m



630364

PSEN op cable axial M12 5-pole 50m



631056

PSEN op pigtail receiver b



631057

PSEN op pigtail receiver m



631055

PSEN op pigtail emitter



631085

PSEN op cable axial M12 12-pole 50m



631083

PSEN op cable axial M12 12-pole 20m



631082

PSEN op cable axial M12 12-pole 10m



631084

PSEN op cable axial M12 12-pole 30m



631080

PSEN op cable axial M12 12-pole 3m



631081

PSEN op cable axial M12 12-pole 5m
