


PSEN op4H-s-30-030/1

630761



Safety light guard, Type 4, PL e, finger protection (resolution 30 mm), protected field height 300 mm, supply voltage 24 V, connector M12, transmitter: 4-pin, receiver: 8-pin, connection cable not supplied with the device.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV
Resolution of safety device:	30 mm
Number of beams:	16
Resolution, protection type:	Bulb
Height of protected field:	300 mm
Operating range (m):	0,2 - 19,0
Reaction time:	11.00 ms
Number of OSSD outputs:	2
Blanking:	Laser pointer
Muting:	Fan
Supply voltage (V):	24,0
Supply voltage type:	DC
Protection type, housing:	IP65
Application in accordance with:	CLC/TS 61496-2;EN 61496-1
Width dimension:	32.3 mm
Height dimension:	383.2 mm
Depth dimension:	36.9 mm
Gross weight:	2440 g
Net weight:	1940 g
Ambient temperature:	0 - 55 °C

Accessories



630303

PSEN op cable axial M12 4-p. shield. 3m



630304

PSEN op cable axial M12 4-p. shield. 5m



630305

PSEN op cable axial M12 4-p. shield. 10m



630306

PSEN op cable angle M12 4-p. shield. 3m



630307

PSEN op cable angle M12 4-p. shield. 5m



630308

PSEN op cable angle M12 4-p. shield. 10m



630309

PSEN op cable axial M12 4-p. shield. 30m



630313

PSEN op cable axial M12 8-p. shield. 3m



630314

PSEN op cable axial M12 8-p. shield. 5m



630315

PSEN op cable axial M12 8-p. shield. 10m



630316

PSEN op cable angle M12 8-p. shield. 3m



630317

PSEN op cable angle M12 8-p. shield. 5m



630318

PSEN op cable angle M12 8-p. shield. 10m



630319

PSEN op cable angle M12 4-p. shield. 30m



630328

PSEN op cable axial M12 8-p. shield. 30m



630329

PSEN op cable angle M12 8-p. shield. 30m