

## PNOZ X4 110VAC 3n/o 1n/c

774734



Safety relay (standalone) Inputs: 1-/2-channel wiring with/without detection of shorts across contacts Outputs: 3 N/O, 1 N/C. Automatic/monitored start UB 110 V DC, width: 45 mm, integral screw terminals, Monitoring E-STOP, safety gates.

### Technical details

|                                          |                                                                                                                                                                 |
|------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certifications:                          | CE;cULus Listed;EAC (Eurasian);TÜV;CCC                                                                                                                          |
| Application options:                     | Instantaneous E-STOP monitoring;Light beam device mon. Type 2 with t/p;Light beam device mon. Type 2 w/o t/p;Light beam device mon. Type 4;Safety gate monitor  |
| Operating modes:                         | Single-channel;Automatic reset;Dual-channel;Manual reset;Detection of shorts across contacts;Monitored manual reset;without detection of shorts across contacts |
| Product standard:                        | EN 60947-5-1                                                                                                                                                    |
| Standards:                               | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1                                                                                                                   |
| Supply voltage (V):                      | 110,0                                                                                                                                                           |
| Supply voltage type:                     | AC                                                                                                                                                              |
| Terminal style:                          | fixed                                                                                                                                                           |
| Terminal type:                           | Screw terminal                                                                                                                                                  |
| Number of instantaneous safety contacts: | 3                                                                                                                                                               |
| Number of delayed safety contacts:       | 0                                                                                                                                                               |
| Number of auxiliary contacts:            | 1                                                                                                                                                               |
| Number of semiconductor outputs:         | 0                                                                                                                                                               |
| Stop category:                           | 0                                                                                                                                                               |
| Max. current at DC13 I (6 cycles/min):   | 7.0 A                                                                                                                                                           |
| Max. current at AC15:                    | 5.0 A                                                                                                                                                           |
| Width dimension:                         | 45.0 mm                                                                                                                                                         |
| Height dimension:                        | 87.0 mm                                                                                                                                                         |

|                      |             |
|----------------------|-------------|
| Depth dimension:     | 121.0 mm    |
| Gross weight:        | 380 g       |
| Net weight:          | 370 g       |
| Ambient temperature: | -10 - 55 °C |

## Optional accessories



774090

COVER P-93