

PSEN 1.1b-22/8mm /10m/ix1/1switch

524129



Magnetic safety switch 2 n/o, square design, with 10 m cable (PUR), height design 13 mm, IP69K, operating distance 8 mm, for applications with PSEN ix1, PU = 1 piece without actuator, certification (TÜV, EAC, UL, ECOLAB approved).

Technical details

| | |
|-----------------------------|---|
| Housing material: | PBT |
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;ECOLAB |
| Sensor principle: | magnetic |
| Number of N/O: | 2 |
| Connection type: | 10m Kabel |
| Switching voltage: | 24 V |
| Type of switching voltage: | DC |
| Assured switching distance: | 8.0 mm |
| Assured release distance: | 26.0 mm |
| Protection type, housing: | IP67;IP69 |
| Status indicator: | Without LED |
| Design: | square |
| Width dimension: | 26.0 mm |
| Height dimension: | 36.0 mm |
| Depth dimension: | 13.0 mm |
| Gross weight: | 360 g |
| Net weight: | 340 g |
| Ambient temperature: | -10 - 70 °C |
| Operating modes: | Series connection |

Accessories



535120

PSEN ix1 Interface for 4 PSEN 1



514120

PSEN 1.1-20 / 1 actuator

Optional accessories



532110

PSEN Winkel / bracket



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



534310

PSEN Distanzplatte / spacer (10 pcs.)



534320

PSEN reverse spacer



535120

PSEN ix1 Interface for 4 PSEN 1
