

PNOZ m ES CANopen

772134



Configurable safe small controllers PNOZmulti 2, fieldbus module, CANopen.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Fieldbus interface:	CANopen
Fieldbus connection:	Male 9-pin D-Sub connector
Fieldbus type:	Slave
Transmission rate:	1 MBit/s;10 kbit/s;125 kBit/s;20 kbit/s;250 kBit/s;50 kbit/s;500 kBit/s;800 kbit/s
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	101.4 mm
Depth dimension:	115.0 mm
Gross weight:	105 g
Net weight:	95 g
Ambient temperature:	0 - 60 °C

Accessories



783542

Spring terminals PNOZ mmcxp, 1 pc.



793542

Screw terminals PNOZ mmcxp, 1 pc.

Optional accessories



779260

PNOZ mm0.xp connector left (10 pcs)



793543

Screw terminals PNOZ mmcxp, 10 pcs.



783543

Spring terminals PNOZ mmcxp, 10 pcs.

Alternatives



772135

PNOZ m ES CC-Link



772138

PNOZ m ES Profinet



772136

PNOZ m ES EtherCAT



772137

PNOZ m ES EtherNet/IP



772132

PNOZ m ES Profibus



772119

PNOZ m ES Powerlink
