

PSEN cs4.2a 1switch

541261



RFID safety switch, 2 safe SC outputs, connection cable 5 m, one actuation direction, IP69K, typ. operating distance 11 mm, Sao = 8mm, Sar = 20 mm, PU = 1 piece uniquely fully coded switch.

Technical details


Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;FCC;IC
Sensor principle:	Transponder
Type of coding:	unique coding
Number of OSSD outputs:	2
Number of inputs:	2
Connection type:	5m Kabel
Supply voltage (V):	24,0
Supply voltage type:	DC
Power consumption DC:	1.0 W
Assured switching distance:	8.0 mm
Assured release distance:	20.0 mm
Protection type, housing:	IP6K9K
Width dimension:	26.0 mm
Height dimension:	37.0 mm
Depth dimension:	18.0 mm
Gross weight:	245 g
Net weight:	218 g
Ambient temperature:	-25 - 70 °C

Accessories



540180

PSEN cs2.1 1 actuator



541180

PSEN cs4.1 1 actuator



541187

PSEN cs4.1 low profile glue 1 actuator



541188

PSEN cs4.1 low profile screw 1 actuator

Optional accessories



540334

PSEN/PDP67 M12-8sm screw terminals



540130

SDD ES ETH



540132

SDD ES PROFIBUS