

## PSEN 1.1p-25/PSEN 1.1-20/8mm/ATEX/ix1

504225



Magnetic safety switch 2 n/o, 4-pin M8 male connector, square design, height design 13 mm, IP67, operating distance 8 mm, for applications with PSEN ix1, PU = 1 piece with actuator, ATEX approval.

### Technical details

Housing material:	PC
Certifications:	CE;cULus Listed;EAC (Eurasian);ATEX;TÜV;ECOLAB;electrosuisse
Sensor principle:	magnetic
Number of N/O:	2
Connection type:	M8, 4pol. male
Switching voltage:	24 V
Type of switching voltage:	DC
Assured switching distance:	8.0 mm
Assured release distance:	26.0 mm
Protection type, housing:	IP65;IP67
Status indicator:	Without LED
Design:	square
Width dimension:	26.0 mm
Height dimension:	42.8 mm
Depth dimension:	13.0 mm
Gross weight:	44 g
Net weight:	36 g
Ambient temperature:	-10 - 55 °C
Operating modes:	Series connection

## Accessories

	533110	PSEN Kabel Winkel/cable angleplug 2m
	533111	PSEN Kabel Gerade/cable straightplug 2m
	533120	PSEN Kabel Winkel/cable angleplug 5m
	533121	PSEN Kabel Gerade/cable straightplug 5m
	533130	PSEN Kabel Winkel/cable angleplug 10m
	533131	PSEN Kabel Gerade/cable straightplug 10m
	533140	PSEN Kabel Winkel/cable angleplug 30m
	533141	PSEN Kabel Gerade/cable straightplug 30m
	535120	PSEN ix1 Interface for 4 PSEN 1

## Optional accessories



532110

PSEN Winkel / bracket



533110

PSEN Kabel Winkel/cable angleplug 2m



533111

PSEN Kabel Gerade/cable straightplug 2m



533120

PSEN Kabel Winkel/cable angleplug 5m



533121

PSEN Kabel Gerade/cable straightplug 5m



533130

PSEN Kabel Winkel/cable angleplug 10m



533131

PSEN Kabel Gerade/cable straightplug 10m



533140

PSEN Kabel Winkel/cable angleplug 30m



533141

PSEN Kabel Gerade/cable straightplug 30m



534310

PSEN Distanzplatte / spacer (10 pcs.)

---



534320

PSEN reverse spacer

---



535120

PSEN ix1 Interface for 4 PSEN 1

---



540310

PSEN screw M4x16 10pcs

---