

PSEN sg2c-5LPKLS-M12/5 switch

570829



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Consisting of 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Push button for accessing & interlocking the safety gate; 3. Key switch (3 positions) 4. Illuminated pushbutton; 5. Section stop pushbutton M12/5 connection with enable switch Delivery scope: Sensing device with pushbuttons (spare part).

Dane

Certyfikacja:	CE;cULus Listed;TÜV;FCC
Zasada działania czujnika:	Transponder
Rodzaj kodowania:	Kodowany
Siła mocująca, kierunek kątowy:	2000 N
Liczba wyjść OSSD:	2
Liczba wejść:	2
Rodzaj przyłącza:	Federzugklemme steckbar
Napięcie zasilania (V):	24,0
Rodzaj napięcia zasilania:	DC
Pobór mocy DC:	2.0 W
Numer przycisku:	2
Stopień ochrony obudowy:	IP54
Liczba elementów sterujących:	4
Liczba wyłączników operacyjnych:	1
Szerokość:	46.5 mm
Wysokość:	568.0 mm
Głębokość:	74.5 mm
Ciężar brutto:	1290 g
Ciężar netto:	1200 g
Temperatura pracy:	-20 - 55 °C

Akcesoria



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)



570890


PSEN sg2 actuator

Akcesoria opcjonalne



401110

PIT en1.0p-5m-s



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)
