

PNOZ ml2p safe link PDP

773602



PNOZmulti Classic, connection module, failsafe, connection for 4 decentralised PDP67 devices, CAN-based, series connection, supply 4 A.

Technical details

Certifications:	CE;cULus Listed;BG;EAC (Eurasian);TÜV;CCC;KCC
Supply voltage (V):	24,0
Power consumption DC:	101.0 W
Version for extreme environ. conditions:	Standard
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	151 g
Net weight:	133 g
Ambient temperature:	0 - 60 °C

Optional accessories

311074

PSS SB BUSCABLE LC



380200

PSS67 Cable M8sf M12sm, 3m



380201

PSS67 Cable M8sf M12sm, 5m

380202

PSS67 Cable M8sf M12sm, 10m



380203

PSS67 Cable M8sf M12sm, 30m



380204

PSS67 Cable M8af M12sm, 3m



380205

PSS67 Cable M8af M12sm, 5m



380206

PSS67 Cable M8af M12sm, 10m



380207

PSS67 Cable M8af M12sm, 30m



380208

PSS67 Cable M12sf M12sm, 3m



380209

PSS67 Cable M12sf M12sm, 5m



380210

PSS67 Cable M12sf M12sm, 10m



380211

PSS67 Cable M12sf M12sm, 30m



380212

PSS67 Cable M12af M12am, 3m



380213

PSS67 Cable M12af M12am, 5m



380214

PSS67 Cable M12af M12am, 10m



380215

PSS67 Cable M12af M12am, 30m



380300

PSEN ma adapter



380301

PSEN cs adapter



380308

PSS67 M12 connector, straight, male, 5pole



380309

PSS67 M12 connector straight, female, 5pole



380310

PSS67 M12 connector, angled, male, 5pole



380311

PSS67 M12 connector, angled, female, 5pole



380316

M12 con., straight, male, 4 pin, D



380317

M12 con., straight, female, 5 pin, L, S



380318

M12 con., straight, male, 5 pin, L, S



380320

PSS67 I/O Cable



783400

PNOZmulti Set spring loaded terminals



793400

PNOZ mi1p/mi2p/mo1p screw terminals