

PIT m3.3p

402240




Electronic operating mode selector switch with transponder key, 2 pushbuttons for switching the operating mode, 2 operating modes, 1 special operating mode.

Technical details

| | |
|----------------------|----------------------------|
| Certifications: | CE;cULus Listed;TÜV;FCC;IC |
| Width dimension: | 98.0 mm |
| Height dimension: | 55.0 mm |
| Depth dimension: | 43.0 mm |
| Gross weight: | 260 g |
| Net weight: | 140 g |
| Ambient temperature: | -20 - 60 °C |

Accessories



402302

PIT m3.2p terminal set spring load












402303

PIT m3.2p screw terminal set angled



402305

PIT m3.2p screw terminal set

| | | |
|---|--------|----------------------------|
|  | 402281 | PIT m3 key2 mode 1 |
|  | 402284 | PIT m3 key2 mode 4 |
|  | 402292 | PIT m3 key2hq mode 2 |
|  | 402291 | PIT m3 key2hq mode 1 |
|  | 402282 | PIT m3 key2 mode 2 |
|  | 402283 | PIT m3 key2 mode 3 |
|  | 402295 | PIT m3 key2hq mode service |
|  | 402293 | PIT m3 key2hq mode 3 |
|  | 402294 | PIT m3 key2hq mode 4 |



402285

PIT m3 key2 mode service
