

PNOZ X7P 110-120VAC 2n/o

777053



Safety relay (standalone) Inputs: 1-channel wiring. Outputs: 2 N/O, Automatic/manual start UB 110 - 120 V AC, width: 22.5 mm, plug-in terminals of screw type Monitoring E-STOP, safety gates.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	110,0 - 120,0
Supply voltage type:	AC
Terminal style:	Plug-in
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	2
Number of delayed safety contacts:	0
Number of semiconductor outputs:	0
Stop category:	0
Max. current at DC13 I (6 cycles/min):	4.0 A
Max. current at AC15:	4.0 A
Width dimension:	22.5 mm
Height dimension:	94.0 mm
Depth dimension:	121.0 mm
Gross weight:	240 g
Net weight:	230 g

Ambient temperature:

-10 - 55 °C

Optional accessories



374280

PNOZ X Set plug in screw terminals P1+P2