

## PSEnsg2c-5CCLLE unit

570836




Safety gate system includes safe interlocking device with guard locking. According to DIN EN60947-5-3. For applications up to SIL CL3 or Ple. Device type: 1. blind cover 2. blind cover 3. illuminated push button 4. illuminated push button 5. E-Stop Scope of delivery: Sensor unit with push buttons including color covers and escape release pin as well as actuator (bolt) for doors with hinges left or right.

## Technical details

|                             |                         |
|-----------------------------|-------------------------|
| Certifications:             | CE;cULus Listed;TÜV;FCC |
| Sensor principle:           | Transponder             |
| Type of coding:             | Coded                   |
| Holding force:              | 2000 N                  |
| Number of OSSD outputs:     | 2                       |
| Number of inputs:           | 2                       |
| Connection type:            | Federzugklemme steckbar |
| Supply voltage (V):         | 24,0                    |
| Supply voltage type:        | DC                      |
| Power consumption DC:       | 2.0 W                   |
| Number of pushbutton:       | 2                       |
| Protection type, housing:   | IP54                    |
| Number of emergency stops:  | 1                       |
| Number of control elements: | 2                       |
| Width dimension:            | 200.0 mm                |
| Height dimension:           | 555.0 mm                |
| Depth dimension:            | 108.0 mm                |
| Gross weight:               | 3050 g                  |
| Net weight:                 | 2670 g                  |
| Ambient temperature:        | -20 - 55 °C             |

## Optional accessories



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)