

PSEN sg2c-5LPKLS-M12/5 unit

570828



Safety gate system, safe interlock and safe guard locking device For applications up to SIL CL 3 and PL e. Consisting of 5 pushbuttons: 1. Illuminated pushbutton for activating the safety gate; 2. Push button for accessing & interlocking the safety gate; 3. Key switch (3 positions) 4. Illuminated pushbutton; 5. Section stop pushbutton M12/5 connection with enable switch Delivery scope: Sensing device with pushbuttons incl. colour caps and Escape release bar and actuator for right or left hinged gates.

Datos técnicos


Certificaciones:	CE;cULus Listed;TÜV;FCC
Principio sensor:	Transpondedor
Tipo de encriptado:	encriptados
Fuerza retención dirección de giro:	2000 N
Número de salidas OSSD:	2
Número de entradas:	2
Tipo de borne:	Federzugklemme steckbar
Tensión alimentación (V):	24,0
Tipo de tensión de alimentación:	DC
Consumo de energía DC:	2.0 W
Número de pulsador:	2
Grado de protección, carcasa:	IP54
Número elementos de mando:	4
Número parada parcial por zonas:	1
Dimensión Ancho:	200.0 mm
Dimensión de altura:	568.0 mm
Dimensión Profundidad:	108.0 mm
Peso bruto:	3060 g
Peso neto:	2690 g
Temperatura ambiente:	-20 - 55 °C

Accesorios opcionales



401110

PIT en1.0p-5m-s



570773

PSEN sg2 cover 2pieces



570777

PSEN sg2c Set spring loaded terminals



570890

PSEN sg2 actuator



570870

PSEN sg escape release pin



570871

PSEN sg auxiliary release pin



570875

PSEN sg color covers (pushbutton)