

PNOZ X13 24VDC 5n/o 1n/c

774549



Safety relay (standalone), inputs: 1/2-channel wiring with/without detection of shorts across contacts, outputs: 5 N/O, 1 N/C, UB 24 V DC, width: 45 mm, screw terminals integrated, monitoring of E-STOP, safety gates.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;CCC
Application options:	Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor
Operating modes:	Single-channel;Automatic reset;Dual-channel;Detection of shorts across contacts;Monitored manual reset
Product standard:	EN 60947-5-1
Standards:	EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1
Supply voltage (V):	24,0
Supply voltage type:	DC
Terminal style:	fixed
Terminal type:	Screw terminal
Number of instantaneous safety contacts:	5
Number of delayed safety contacts:	0
Number of auxiliary contacts:	1
Number of semiconductor outputs:	0
Stop category:	0
Max. current at DC13 I (6 cycles/min):	7.0 A
Max. current at AC15:	5.0 A
Width dimension:	45.0 mm
Height dimension:	87.0 mm
Depth dimension:	121.0 mm
Gross weight:	355 g

Net weight:

345 g

Ambient temperature:

-10 - 55 °C

Optional accessories



774090

COVER P-93