

PMI 516

264516



PMIopen, operator panel, 3.5", resolution 320 x 240 pixels, analogueresistive touch-screen, TFT, RAM 256 MB, Flash 512 MB, SD card, 1 D-sub connector RS232 9-pin, 1 RJ45 port 100 MBit/s, 1 USB slave, 2 USB host, battery-buffered real-time clock, 24 V DC, 6,5 W, open HMI platform for any common visualisation software, configurable via PMI Assistant.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Resolution:	640 x 480
Display type:	TFT
Display diagonal:	6.5 Zoll
Colour depth:	65536
Touchscreen:	Resistive
Possible PMI applications:	PSS/PSSu/PNOZmulti;PNOZmulti diagnostics;Diagnostics PSS / SafetyBUSp
Number of Ethernet interfaces:	1
Number of RS 232 interfaces:	1
Supply voltage (V):	24,0
Supply voltage type:	DC
Operating system:	Windows Embedded CE 6.0
Width dimension:	212.0 mm
Height dimension:	165.0 mm
Depth dimension:	62.5 mm
Gross weight:	2372 g
Net weight:	1344 g
Ambient temperature:	0 - 50 °C

Optional accessories




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



269701

seal for PMlvisu, PMlopen, PMlmicro



310300

Serial programming cable



313100

SD Memory Card 512MB

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI

265220

Zenon Operator 7.20 RT PMI



THE SPIRIT OF SAFETY

265020

Zenon Operator 7.20 Dev 1024
