

PMI 638 Control

264638



PMIcontrol - Control panel with 15" touchscreen, CODESYS runtime and TargetVisu installed/licensed, mastersystems: CANopen, ModbusTCP.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Resolution:	1024 x 768
Display type:	TFT
Colour depth:	16,2 M
Touchscreen:	Resistive
Display diagonal:	15.0 Zoll
Possible PMI applications:	PSS/PSSu/PNOZmulti;PNOZmulti diagnostics;Diagnostics PSS / SafetyBUSp
Number of Ethernet interfaces:	1
Number of RS 232 interfaces:	1
Number of USB host interfaces:	2
Supply voltage (V):	24,0
Supply voltage type:	DC
Operating system:	Windows Embedded Compact 7
Width dimension:	412.0 mm
Height dimension:	332.0 mm
Depth dimension:	81.9 mm
Gross weight:	6860 g
Net weight:	4510 g
Ambient temperature:	0 - 50 °C

Optional accessories




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



310300

Serial programming cable

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI