



PMIvisu, operator terminal with 7" capacitive touch-screen, preinstalled software PASvisu Server, PASvisu Viewer PMI, PSS 4000 firmware (OPC Server).

## Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Resolution:	800 x 480
Display type:	TFT
Colour depth:	16,2 M
Display diagonal:	7.0 Zoll
Possible PMI applications:	PSS/PSSu/PNOZmulti;PNOZmulti diagnostics;Diagnostics PSS / SafetyBUSp
Number of Ethernet interfaces:	1
Number of RS 232 interfaces:	1
Number of USB host interfaces:	2
Supply voltage (V):	24,0
Supply voltage type:	DC
Operating system:	Windows Embedded Compact 7
Width dimension:	216.0 mm
Height dimension:	153.0 mm
Depth dimension:	65.4 mm
Gross weight:	2400 g
Net weight:	1390 g
Ambient temperature:	0 - 50 °C

## Optional accessories




261905

RT-Licence PVIS OPC-Srv f.PMI, PtoP



261906

RT-Licence PVIS OPC-Srv f.PMI, 8 devices



269700

power connector PMI (3 pcs)



269701

seal for PMIvisu, PMlopen, PMImicro



310300

Serial programming cable



313100

SD Memory Card 512MB

265010

Zenon Operator Dev 1024

265210

Zenon Operator RT PMI

## Related Products



265352

PASvisu RT Clients 1 PMI



265362

PASvisu RT Logging PMI



265456

PASvisu RT Variables 500 PMI



265461

PASvisu RT Variables 1000 PMI



265466

PASvisu RT Variables 2000 PMI