

PSS67 IO1 16FDI

316010



PSS 4000 I/O, I/O module with protection type IP67, 16 safe digital inputs, connection SafetyNET p.

Technical details

Certifications:	CE;cULus Listed;TÜV
Protection type, housing:	IP67
Ambient temperature:	-30 - 70 °C
Width dimension:	61.5 mm
Height dimension:	260.0 mm
Depth dimension:	52.0 mm
Net weight:	940 g

Accessories



313110

PSSu A Con 1/4 S (2 pcs.)



313111

PSSu A Con 2/8 C (2 pcs.)

Optional accessories



312065

PSSu H m F DP SN SD



312085

PSSu H FS SN SD



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



313100

SD Memory Card 512MB



380000

SafetyNET p Cable per mtr



380001

SN CAB RJ45s RJ45s, 0,5m



380003

SN CAB RJ45s RJ45s, 1m



380005

SN CAB RJ45s RJ45s, 2m



380007

SN CAB RJ45s RJ45s, 5m



380009

SN CAB RJ45s RJ45s, 10m



380400

SafetyNET p Connector RJ45s



380600

PSSnet SLL 5T



380650

PSSnet SHL 6T 2FSMSC MRP



380604

PSSnet SLL 4T 1FMMSM



312071

PSSu H PLC1 FS DP SN SD



314085

PSSu H FS SN SD-T



312066

PSSu H m F DPsafe SN SD



314071

PSSu H PLC1 FS SN SD M12-T
