

PSS67 PLC1 16FDI

316020



PLC Module IP67 w/ 16 failsafe Inputs, SNp

## Technical details

Certifications:	CE;cULus Listed;TÜV
Protection type, housing:	IP67
Application range:	Standard/failsafe
Width dimension:	61.5 mm
Height dimension:	260.0 mm
Depth dimension:	52.0 mm
Net weight:	940 g
Ambient temperature:	-30 - 70 °C

## Accessories



380321

PSS67 Supply cable



380327

Supply cable 5x1.5

## Optional accessories



380000

SafetyNET p Cable per mtr



380208

PSS67 Cable M12sf M12sm, 3m



380209

PSS67 Cable M12sf M12sm, 5m



380210

PSS67 Cable M12sf M12sm, 10m



380211

PSS67 Cable M12sf M12sm, 30m



380212

PSS67 Cable M12af M12am, 3m



380213

PSS67 Cable M12af M12am, 5m



380214

PSS67 Cable M12af M12am, 10m



380215

PSS67 Cable M12af M12am, 30m



380300

PSEN ma adapter



380301

PSEN cs adapter



380308

PSS67 M12 connector, straight, male, 5pole



380309

PSS67 M12 connector straight, female, 5pole



380310

PSS67 M12 connector, angled, male, 5pole



380311

PSS67 M12 connector, angled, female, 5pole



380316

M12 con., straight, male, 4 pin, D



380317

M12 con., straight, female, 5 pin, L, S



380318

M12 con., straight, male, 5 pin, L, S



380320

PSS67 I/O Cable



380400

SafetyNET p Connector RJ45s

---



380324

Caps for IP67 moduls

---



328835

µSD Card 512MB industrial

---

316011

PSS67 Cap 7/8"

---



380071

Crimping Tool

---