

PSSu E F AI I-T

314260



PSSu, electronic module, failsafe, analogue inputs and outputs, 1 input, 0 - 25.59 mA, dual-pole, differential input, resolution 12 Bit, for increased environmental requirements.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA
Application range:	Failsafe
Number of analogue inputs:	1
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/12C-T;PSSu BP 1/12S-T;PSSu BP 1/8C-T;PSSu BP 1/8S-T;PSSu BP-C 1/12C-T;PSSu BP-C 1/12S-T;PSSu BP-C 1/8C-T;PSSu BP-C 1/8S-T
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	45 g
Net weight:	37 g
Ambient temperature:	-40 - 70 °C

Accessories



312410

PSSu E S 2DO 2



314600

PSSu BP 1/8 S-T



314601

PSSu BP 1/8 C-T



314610

PSSu BP-C 1/8 S-T



314611

PSSu BP-C 1/8 C-T



314618

PSSu BP 1/12 S-T

314619

PSSu BP 1/12 C-T



314620

PSSu BP-C 1/12 S-T



314621

PSSu BP-C 1/12 C-T

Optional accessories



312958

PSSu A LA0 (10 x 108 pcs.)