

## PSSu E F INC-T

314280



PSSu, electronic module, failsafe, counter, 2 operating modes, configurable, 1 input, incremental encoder, differential signal RS422, resolution 32 Bit, for increased environmental requirements.

## Technical details

|                           |   |
|---------------------------|---|
| Certifications:           | CE;cULus Listed;EAC (Eurasian);TÜV                                  |
| Application range:        | Failsafe  |
| Protection type, housing: | IP20  |
| Permitted base modules:   | PSSu BP 2/16C-T;PSSu BP 2/16S-T;PSSu BP-C 2/16C-T;PSSu BP-C 2/16S-T |
| Width dimension:          | 25.4 mm   |
| Height dimension:         | 76.0 mm   |
| Depth dimension:          | 60.2 mm   |
| Gross weight:             | 65 g  |
| Net weight:               | 51 g  |
| Ambient temperature:      | -40 - 70 °C   |

## Accessories



314628

PSSu BP 2/16 S-T



314629

PSSu BP 2/16 C-T



314630

PSSu BP-C 2/8 S-T



314631

PSSu BP-C 2/8 C-T

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312902

PSSu A EC



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)