

PSSu E S 2AI TC-T

314500



PSSu, electronic module, standard, analogue inputs and outputs, 2 inputs, thermocouples with letter codes R, S, B, J, T, E, K, N, voltage with ranges -30 - 30 mV, -60 - 60 mV, -120 - 120 mV, reference temperature via special base modules using integrated Pt1000, for increased environmental requirements.

Technical details

Certifications:	CE;cULus Listed;TÜV
Application range:	Standard
Number of analogue inputs:	2
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 1/8C-TJ;PSSu BP 1/8S-TJ;PSSu BP-C 1/8C-TJ;PSSu BP-C 1/8S-TJ
Width dimension:	12.6 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	44 g
Net weight:	36 g
Ambient temperature:	-40 - 70 °C

Accessories



314602

PSSu BP 1/8 S-TJ

314603

PSSu BP 1/8 C-TJ



314612

PSSu BP-C 1/8 S-TJ



314613

PSSu BP-C 1/8 C-TJ

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T