

## PSSu E S 4DI-T

314400



PSSu, electronic module, standard, digital inputs and outputs, 4 inputs, , for increased environmental requirements.

## Technical details

|                           |   |
|---------------------------|---|
| Certifications:           | CE;cULus Listed   |
| Application range:        | Standard  |
| Number of digital inputs: | 4   |
| Protection type, housing: | IP20  |
| Permitted base modules:   | PSSu BP 1/12C-T;PSSu BP 1/12S-T;PSSu BP 1/8C-T;PSSu BP 1/8S-T;PSSu BP-C 1/8C-T;PSSu BP-C 1/8S-T;PSSu BP-C1 1/12C-T;PSSu BP-C1 1/12S-T |
| Width dimension:          | 12.6 mm   |
| Height dimension:         | 76.0 mm   |
| Depth dimension:          | 60.2 mm   |
| Gross weight:             | 40 g  |
| Net weight:               | 31 g  |
| Ambient temperature:      | -40 - 70 °C   |

## Accessories



314600

PSSu BP 1/8 S-T



314601

PSSu BP 1/8 C-T



314610

PSSu BP-C 1/8 S-T



314611

PSSu BP-C 1/8 C-T



314618

PSSu BP 1/12 S-T



314622

PSSu BP-C1 1/12 S-T



314623

PSSu BP-C1 1/12 C-T

## Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T