


PSSu E S INC 24V se -T

314486



PSSu, electronic module, standard, counter, 2 operating modes, configurable, 1 input, incremental encoder, differential signal RS422, resolution 32 Bit, 1 output encoder supply 24 V DC 100 mA, 1 output, 0.5 A, for increased environmental requirements.

Technical details

Certifications:	CE;TÜV
Application range:	Standard
Protection type, housing:	IP20
Permitted base modules:	PSSu BP 2/16C;PSSu BP 2/16S;PSSu BP-C 2/16C;PSSu BP-C 2/16S
Width dimension:	25.2 mm
Height dimension:	76.0 mm
Depth dimension:	60.2 mm
Gross weight:	57 g
Net weight:	48 g
Ambient temperature:	-40 - 70 °C

Accessories



314628

PSSu BP 2/16 S-T



314629

PSSu BP 2/16 C-T



314630

PSSu BP-C 2/8 S-T



314631

PSSu BP-C 2/8 C-T

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T