

CIRCUIT-BREAKER VL 630N STANDARD BREAKING CAPACITY ICU=55KA / 415 V AC 3 POLE, LINE PROTECTION ELECTRONIC TRIP UNIT ETU20, LSI IN=630A, RATED CURRENT IR=252-630A, OVERLOAD ISD=1,5TO9XIR, II=10XIN SHORT-CIRCUIT

Model		
Type of the driving mechanism / motor drive		No
Design of the overcurrent release		ETU20
General technical data		
Number of poles		3
Size of the circuit-breaker		3VL5
Electrical endurance (switching cycles) / typical		5 000
Usage category		A
Performance class for circuit breaker		N
Mechanical service life (switching cycles) / typical		10 000
Equipment marking / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750		Q
Operating frequency / maximum	1/s	60
Voltage		
Rated operational voltage Ue / max.	V	690
Insulation voltage		
• rated value	V	800
• at AC / rated value	V	800
Surge voltage resistance / rated value	kV	8
Protection class		
Protection class IP		IP20
Protective function of the overcurrent release		LSI
Dissipation		
Power loss [W]		
• maximum	W	160
Electricity		
Continuous current / rated value	A	630
Derating temperature / for the rated value of the continuous current	°C	50
Adjustable pick-up value current		

- of the current-dependent overload release / Full-scale value
- of instantaneous short-circuit trip unit / initial value
- of instantaneous short-circuit trip unit / Full-scale value

A	630
A	6 300
A	6 300

Main circuit

Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• for main current circuit / at AC / at 50 Hz / maximum	V	690
• for main current circuit / at AC / at 60 Hz / maximum	V	690
Operating current		
• at 40 °C / rated value	A	630
• at 50 °C / rated value	A	630
• at 55 °C / rated value	A	598.5
• at 60 °C / rated value	A	598.5
• at 65 °C / rated value	A	504
• at 70 °C / rated value	A	504

Auxiliary circuit

Number of CO contacts / for auxiliary contacts		0
Number of NC contacts / for auxiliary contacts		1
Number of NO contacts / for auxiliary contacts		2

Suitability

Suitability for use		system/generator protection
----------------------------	--	-----------------------------

Adjustable parameters

Adjustable pick-up value current / of the current-dependent overload release / initial value	A	252
---	---	-----

Product details

Product component		
• Trip indicator		Yes
• Auxiliary switch		Yes
• Voltage trigger		No
• undervoltage release		Yes
• undervoltage release with leading contact		No
Product extension / optional / motor drive		Yes

Product function

Product function		
-------------------------	--	--

- of thermal overload trip unit
- Ground fault protection
- for neutral conductors / Short-circuit and overload proof
- Overload protection

adjustable
No
No
Yes

Short circuit

Operational short-circuit current breaking capacity (Ics)

• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 500 V / rated value	kA	20
• at 690 V / rated value	kA	10

Maximum short-circuit current breaking capacity (Icu)

• at 240 V / rated value	kA	65
• at 415 V / rated value	kA	55
• at 440 V / rated value	kA	35
• at 480 V / acc. to NEMA / rated value	kA	25
• at 500 V / rated value	kA	25
• at 600 V / acc. to NEMA / rated value	kA	20
• at 690 V / rated value	kA	20

Connections

Arrangement of electrical connectors / for main current circuit

front side

Type of electrical connection / for main current circuit

screw-type terminals

Mechanical Design

Height	mm	279.5
Width	mm	190
Depth	mm	138.5
Mounting type		fixed mounting

Environmental conditions

Ambient temperature

• during operation / minimum	°C	-25
• during operation / maximum	°C	70
• during storage / minimum	°C	-40
• during storage / maximum	°C	80

Certificates

Certificate of suitability		IEC, standard switching capacity (N)
Equipment marking		
• acc. to DIN EN 61346-2		Q

General Product Approval	EMC	Declaration of Conformity
--------------------------	-----	---------------------------



[sonstig](#)



[TSE](#)



Test Certificates	Shipping Approval	other
-------------------	-------------------	-------

[spezielle Prüfbescheinigung](#)
[n](#)



[Bestätigungen](#)

[Umweltbestätigung](#)

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/3VL5763-1SE36-2PE1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/3VL5763-1SE36-2PE1/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3VL5763-1SE36-2PE1

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>

last modified:

08/30/2016