

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7108-5SF70-4BG0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed	3,000 rpm
Number of poles	10
Rated torque (100 K)	60.0 Nm
Rated current	38.00 A
Static torque (60 K)	74.0 Nm
Static torque (100 K)	91.0 Nm
Stall current (60 K)	46.00 A
Stall current (100 K)	57.00 A
Rotor moment of inertia	248.00 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.60 Nm/A
Voltage constant at 20° C	101.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.04 Ω
Rotary field inductance	1.1 mH
Electrical time constant	26.00 ms
Mechanical time constant	1.30 ms
Thermal time constant	60 min
Shaft torsional stiffness	96,000 Nm/rad
Net weight of the motor	64.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	100
Cooling	Forced ventilation
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.100 mm
Axial runout tolerance	0.100 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (new flange design)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45
Electrical connection	Axial DE
Connector size	3

Optimum operating point

Optimum speed	3,000 rpm
Optimum power	18.8 kW

Limiting data

Max. permissible speed (mech.)	6,000 rpm
Max. permissible speed (inverter)	5,600 rpm
Maximum torque	280.0 Nm
Maximum current	205.00 A

Recommended Motor Module

Rated inverter current	60.00 A
Maximum inverter current	113.00 A
Maximum torque	177.0 Nm