



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8184-1HD10-2ED2-Z**
L76+V92

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	44.0	365.0	86.0	390	39.0	1,150	925	205.0	5,000	365.0	86	0.928	0.82	42.0
	BLM/SLM 400V	39.0	372.0	87.0	340	34.0	1,000	925	205.0	5,000	372.0	87	0.920	0.83	42.0
	ALM/BLM/SLM 480V	50.0	354.0	84.0	450	45.7	1,350	925	205.0	5,000	354.0	84	0.936	0.82	41.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	180
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft extension	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	22 min
Moment of inertia	4,890 kgcm ²
Weight (approx.)	350 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7322-P05

Cooling data and sound pressure level

Airflow, min.	0.17 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	550 Pa

Special design

L76	EC fan 400 V 3 AC 50/60 Hz
V92	1PH7184-/1PL6184-compatible shaft extension 60 mm x 140 mm

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 5000 rpm