



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8135-2FG02-0BA1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		P <sub>N</sub> [kW]	M <sub>N</sub> [Nm]	I <sub>N</sub> [A]	U <sub>N</sub> [V]	f <sub>N</sub> [Hz]	n <sub>N</sub> [rpm]	M <sub>max</sub> [Nm]	I <sub>max</sub> [A]	n <sub>max</sub> [rpm]	M <sub>0</sub> [Nm]	I <sub>0</sub> [A]	η	cos φ	I <sub>μ</sub> [A]
Y	ALM 400V	35.6	148.0	59.0	407	76.7	2,300	390	179.0	4,500	158.0	63	0.953	0.00	0.0
	BLM/SLM 400V	31.4	150.0	59.0	356	66.7	2,000	390	179.0	4,500	158.0	63	0.953	0.00	0.0
	ALM/BLM/SLM 480V	40.2	145.0	58.0	449	88.3	2,650	390	179.0	4,500	158.0	63	0.952	0.00	0.0

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Shaft height	132
Cooling	Forced ventilation DE -> NDE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard with fixed bearing
Shaft extension	Plain shaft
Encoder system	Absolut encoder 22 bit Singleturn + 12 bit Multiturn, max. encoder speed = 12000 rpm

### Physical constants

Thermal time constant	10 min
Moment of inertia	750 kgcm <sup>2</sup>
Weight (approx.)	120 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Cooling data and sound pressure level

Airflow, min.	0.09 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	140 Pa

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm