



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8226-1DC30-1ED1

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		$P_N$ [kW]	$M_N$ [Nm]	$I_N$ [A]	$U_N$ [V]	$f_N$ [Hz]	$n_N$ [rpm]	$M_{max}$ [Nm]	$I_{max}$ [A]	$n_{max}$ [rpm]	$M_0$ [Nm]	$I_0$ [A]	$\eta$	$\cos \phi$	$I\mu$ [A]
Y	ALM 400V	118.0	1,409.0	235.0	350	27.5	800	2,300	395.0	4,500	1,409.0	235	0.918	0.90	71.0
	BLM/SLM 400V	106.0	1,446.0	240.0	310	24.2	700	2,300	395.0	4,500	1,446.0	240	0.907	0.90	71.0
	ALM/BLM/SLM 480V	146.0	1,394.0	230.0	440	34.1	1,000	2,300	395.0	4,500	1,394.0	230	0.932	0.89	74.0

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Open circuit cooling DE-> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Increased cantilever forces
Shaft extension	Feather key with full key balancing
Encoder system	Incremental encoder 22 bit with commutation position 11 bit, max. encoder speed = 12000 rpm

### Physical constants

Thermal time constant	23 min
Moment of inertia	19,300 kgcm <sup>2</sup>
Weight (approx.)	740 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7422-P06

### Cooling data and sound pressure level

Airflow, min.	0.33 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	600 Pa

<sup>1)</sup> at a rated frequency of 2 kHz and a speed range of up to 2000 rpm