

## Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7046-5AH71-1DGO



Figure similar

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

Rated speed	4,500 rpm
Number of poles	6
Rated torque (100 K)	2.4 Nm
Rated current	3.20 A
Static torque (60 K)	6.0 Nm
Static torque (100 K)	7.0 Nm
Stall current (60 K)	6.90 A
Stall current (100 K)	8.10 A
Rotor moment of inertia	7.52 kgcm <sup>2</sup>
Efficiency	90.0 %

### Physical constants

Torque constant	0.87 Nm/A
Voltage constant at 20° C	55.5 V/1000*min <sup>-1</sup>
Winding resistance at 20° C	0.41 Ω
Rotary field inductance	2.9 mH
Electrical time constant	7.00 ms
Mechanical time constant	1.20 ms
Thermal time constant	35 min
Shaft torsional stiffness	8,300 Nm/rad
Net weight of the motor	9.3 kg

### Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	48
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.080 mm
Axial runout tolerance	0.080 mm
Vibration severity grade	Grade A
Degree of protection	IP64
Design acc. to Code I	IM B5 (compatible with 1FT6)
Temperature monitoring	Pt1000 temperature sensor
Color of the housing	Standard (pearl dark gray similar to RAL 9023)
Shaft end type	Plain shaft
Sensor design	Encoder IC22DQ: incremental encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + commutation position 11 bits
Electrical connection	Connector turnable
Connector size	1

### Optimum operating point

Optimum speed	3,500 rpm
Optimum power	1.3 kW

### Limiting data

Max. permissible speed (mech.)	9,000 rpm
Max. permissible speed (inverter)	9,000 rpm
Maximum torque	31.0 Nm
Maximum current	38.00 A

### Recommended Motor Module

Rated inverter current	9.00 A
Maximum inverter current	27.00 A
Maximum torque	22.4 Nm