



Figure similar

## Data sheet for SIMOTICS M-1PH8

Article No. : **1PH8137-1HF10-0GA1-Z**  
V90

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Engineering data

		P <sub>N</sub> [kW]	M <sub>N</sub> [Nm]	I <sub>N</sub> [A]	U <sub>N</sub> [V]	f <sub>N</sub> [Hz]	n <sub>N</sub> [rpm]	M <sub>max</sub> [Nm]	I <sub>max</sub> [A]	n <sub>max</sub> [rpm]	M <sub>0</sub> [Nm]	I <sub>0</sub> [A]	η	cos φ	I <sub>μ</sub> [A]
Y	ALM 400V	25.0	136.0	56.0	353	59.6	1,750	380	151.0	8,000	172.0	68	0.907	0.84	23.1
	BLM/SLM 400V	22.0	140.0	56.0	308	51.3	1,500	380	151.0	8,000	172.0	68	0.904	0.84	24.2
	ALM/BLM/SLM 480V	28.0	134.0	55.0	401	67.9	2,000	380	151.0	8,000	172.0	68	0.931	0.84	23.1

### Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	132
Cooling	Forced ventilation NDE -> DE
Vibration severity grade	R/A
Shaft and flange accuracy	R
Degree of protection	IP55
Design acc. to Code I	IM B3 (IM V5, IM V6, IM B6, IM B7, IM B8)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Plain shaft
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

### Physical constants

Thermal time constant	30 min
Moment of inertia	1,090 kgcm <sup>2</sup>
Weight (approx.)	141 kg

### Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	right
Signal connection	DE
Terminal box designation	gk833

### Cooling data and sound pressure level

Airflow, min.	0.09 m <sup>3</sup> /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	70 dB <sup>1)</sup>
Air discharge	axial
Pressure drop	140 Pa

### Special design

V90 1PH7-compatible shaft extension 42 mm x 110 mm

<sup>1)</sup> at a rated frequency of 4 kHz and a speed range of up to 5000 rpm