



Figure similar

Data sheet for SIMOTICS S-1FT7

Article No. : 1FT7068-5AF70-1BA5

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

| | |
|-------------------------|-------------------------|
| Rated speed | 3,000 rpm |
| Number of poles | 10 |
| Rated torque (100 K) | 10.9 Nm |
| Rated current | 6.70 A |
| Static torque (60 K) | 13.0 Nm |
| Static torque (100 K) | 15.0 Nm |
| Stall current (60 K) | 7.30 A |
| Stall current (100 K) | 8.30 A |
| Rotor moment of inertia | 23.20 kgcm ² |
| Efficiency | 92.0 % |

Physical constants

| | |
|-----------------------------|--------------------------------|
| Torque constant | 1.78 Nm/A |
| Voltage constant at 20° C | 113.0 V/1000*min ⁻¹ |
| Winding resistance at 20° C | 0.54 Ω |
| Rotary field inductance | 6.4 mH |
| Electrical time constant | 12.00 ms |
| Mechanical time constant | 1.20 ms |
| Thermal time constant | 45 min |
| Shaft torsional stiffness | 21,500 Nm/rad |
| Net weight of the motor | 16.3 kg |

Mechanical data

| | |
|--------------------------|--|
| Motor type | Permanent-magnet synchronous motor |
| Motor type | Compact |
| Shaft height | 63 |
| Cooling | Natural cooling |
| Radial runout tolerance | 0.040 mm |
| Concentricity tolerance | 0.100 mm |
| Axial runout tolerance | 0.100 mm |
| Vibration severity grade | Grade R |
| Degree of protection | IP67 |
| Design acc. to Code I | IM B5 (new flange design) |
| Temperature monitoring | Pt1000 temperature sensor |
| Color of the housing | Standard (pearl dark gray similar to RAL 9023) |
| Shaft end type | Fitted key and keyway |
| Sensor design | Encoder AS24DQI: Absolut encoder Singleturn 24 bit - with signal connection RJ45 |
| Electrical connection | Connector turnable |
| Connector size | 1 |

Optimum operating point

| | |
|---------------|-----------|
| Optimum speed | 3,000 rpm |
| Optimum power | 3.4 kW |

Limiting data

| | |
|-----------------------------------|-----------|
| Max. permissible speed (mech.) | 9,000 rpm |
| Max. permissible speed (inverter) | 5,100 rpm |
| Maximum torque | 63.0 Nm |
| Maximum current | 43.00 A |

Recommended Motor Module

| | |
|--------------------------|---------|
| Rated inverter current | 9.00 A |
| Maximum inverter current | 27.00 A |
| Maximum torque | 46.0 Nm |