

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1094A

SIMOTICS GP - 90 L - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
230	Δ	50	2.20	-/-	8.20	2855	7.4	79.7	80.9	81.3	0.85	0.77	0.65	6.5	2.8	3.2	IE1
400	Y	50	2.20	-/-	4.70	2855	7.4	79.7	80.9	81.3	0.85	0.77	0.65	6.5	2.8	3.2	IE1
460	Y	60	2.54	-/-	4.55	3450	7.1	81.5	81.5	80.2	0.86	0.81	0.70	7.0	2.8	3.3	IE1

IM B5 / IM 3001	FS 90 L	kg	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	---------	----	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1,000 m

Locked rotor time (hot / cold) : 5.94 s | 11.2 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64.0 / 75.0 dB(A) ²⁾	67.0 / 78.0 dB(A) ²⁾	External earthing terminal	No
Moment of inertia	0.0046 kg m ²		Vibration severity grade	A
Bearing DE NDE	6205 2Z C3	6004 2Z C3	Insulation	155(F) to 130(B)
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	-/-		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	1.5 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Type of terminal box	TB1 E00	Cable entry	1xM25x1,5
Contact screw thread	M4	Cable gland	1 plug


Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>
-------------------------------	---------------------	-------------------------------	-------------	---

	document type datasheet	document status released	customer	
	title 1LE1002-0EA42-2FA4-Z D22	document number	rev. 01	creation date 2021-04-23 13:00
© Siemens AG 2021				Page 1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1094A

SIMOTICS GP - 90 L - IM B5 - 2p

Special design

D22 motor without CE character for export outside the EEA (see EU regulation 640/2009)

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	<i>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</i>			
SIEMENS	document type datasheet	document status released		customer			
	title 1LE1002-0EA42-2FA4-Z D22	document number					
© Siemens AG 2021	rev. 01	creation date 2021-04-23 13:00	language en	Page 2/2			