

TRANSFORMER SITAS;  
 PHASES:1;  
 PN/PN(S6)(KVA):0,25 /0,85;  
 UPRI(V):400+/-5%;  
 USEC(V):230;  
 ISEC(A):1,09;  
 F(HZ):50...60;  
 VECTOR GR./SHIELD WNG.:li0 /0;  
 TA/ISOKL:40 /B;  
 IP00;  
 TYPE OF TERMINALS:CAGE-CLAMP;  
 INSTALLATION:SCREWS/MOUNTING RAILS;  
 EN 61558-2-1, -2-2,  
 -2-4 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT  
 TRANSFORMER< >ISOLATION TRANSFORMER<

**General technical details:**

<b>Product designation</b>		transformer SITAS
<b>product brand name</b>		SIDAC
<b>Operating apparent output / rated value</b>	V·A	250
<b>Efficiency</b>		0.89
<b>Manner of switching for transformers</b>		li0
<b>Verification of suitability</b>		CE / cRUus
<b>Product function</b>		
• temperature surveillance		No
• isolation control		No
• short circuit and overload protection		No
<b>Number of the protective coils</b>		0
<b>Short-term vector power</b>	V·A	850
<b>Relative short-circuit voltage</b>	%	5.4

**Inputs:**

<b>Phase number / of the inputs</b>		1
<b>Input voltage</b>		
• _1 / rated value	V	420
• _2 / rated value	V	400
• _3 / rated value	V	380
<b>Electrical input frequency</b>		
• minimum	Hz	50
• maximum	Hz	60

**Outputs:**

<b>Phase number / of the outputs</b>		1
<b>Output voltage</b>		
• _1 / rated value	V	230
<b>Electrical output frequency</b>		
• maximum	Hz	60
• minimum	Hz	50

**Ambient conditions:**

<b>Thermal class / according to IEC 60085</b>		B
<b>Ambient temperature / rated value</b>	°C	40
<b>Protection class IP</b>		IP00

**Mechanical design:**

<b>Design of the electrical connection</b>		
• secondary side / for main current circuit		Cage-Clamp terminals
• at the input / for main current circuit		Cage Clamp terminals
<b>Mounting type</b>		screws / standard rail
<b>Construction form of the iron core</b>		EI 96/58
<b>Width</b>	m	0.098
<b>Height</b>	m	0.106
<b>Depth</b>	m	0.118

**Certificates/approvals:**

General Product Approval

Shipping Approval

other



GOST



PRS

[other](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/industrial-controls/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/industrial-controls/mall>**CAX-Online-Generator**<http://www.siemens.com/cax>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/4AM4042-5AT10-0FA1/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4AM4042-5AT10-0FA1](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AM4042-5AT10-0FA1)**last change:**

Dec 5, 2011