

TRANSFORMER SITAS;
 PHASES:1;
 PN/PN(S6)(KVA):0,315 /1,12;
 UPRI(V):400+/-5%;
 USEC(V):24;
 ISEC(A):13,1;
 F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:li0 /0;
 TA/ISOKL:40 /B;
 IP00;
 TYPE OF TERMINALS:SCREW/TAB CONNECTION;
 INSTALLATION:MOUNTING RAILS;
 EN 61558-2-2,
 -2-6 >UL/CSA-RECOGNIZED< >CONTROL CIRCUIT
 TRANSFORMER< >SAFETY ISOLATING
 TRANSFORMER<

General technical details:

Product designation		transformer SITAS
product brand name		SIDAC
Operating apparent output / rated value	V-A	315
Efficiency		0.9
Manner of switching for transformers		li0
Verification of suitability		CE / cRUus
Product function		
<ul style="list-style-type: none"> temperature surveillance 		No
<ul style="list-style-type: none"> isolation control 		No
<ul style="list-style-type: none"> short circuit and overload protection 		No
Number of the protective coils		0
Short-term vector power	V-A	1,120
Relative short-circuit voltage	%	5.93

Inputs:

Phase number / of the inputs		1
Input voltage		
<ul style="list-style-type: none"> _1 / rated value 	V	420
<ul style="list-style-type: none"> _2 / rated value 	V	400
<ul style="list-style-type: none"> _3 / rated value 	V	380
Electrical input frequency		
<ul style="list-style-type: none"> minimum 	Hz	50

- maximum

Hz	60
----	----

Outputs:

Phase number / of the outputs		1
--------------------------------------	--	---

Output voltage		
-----------------------	--	--

- _1 / rated value

V	24
---	----

Electrical output frequency		
------------------------------------	--	--

- maximum
- minimum

Hz	60
Hz	50

Ambient conditions:

Thermal class / according to IEC 60085		B
---	--	---

Ambient temperature / rated value	°C	40
--	----	----

Protection class IP		IP00
----------------------------	--	------

Mechanical design:

Design of the electrical connection		
--	--	--

- secondary side / for main current circuit
- at the input / for main current circuit

screw-type terminals / tab terminals
screw-type terminals / tab terminals

Mounting type		standard rail
----------------------	--	---------------

Construction form of the iron core		EI 105/60
---	--	-----------

Width	m	0.107
--------------	---	-------

Height	m	0.111
---------------	---	-------

Depth	m	0.12
--------------	---	------

Certificates/approvals:

General Product Approval	Shipping Approval	other
---------------------------------	--------------------------	--------------



[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

CAX-Online-Generator

<http://www.siemens.com/cax>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/4AM4342-5AN00-0EB0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AM4342-5AN00-0EB0

last change:

Dec 5, 2011