

LIF 1,5F638 R**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Insulated tab-connector sleeves made from PVC
with copper sleeve**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 0.5 mm ² - 1.5 mm ²
Order No.	9200540000
Type	LIF 1,5F638 R
GTIN (EAN)	40322484 10385
Qty.	100 pc(s).

Creation date March 30, 2021 12:51:31 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

Data sheet

LIF 1,5F638 R

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	7.7 mm	Depth (inches)	0.303 inch
Net weight	0.95 g	Width	20.8 mm
Width (inches)	0.819 inch		

Technical data

Description of article	Insulated tab-connector sleeves 1.5 mm ² / 6.3x0.8
------------------------	---

Connectors

Conductor cross-section, max.	1.5 mm ²	Conductor cross-section, min.	0.5 mm ²
Dimension	6.3 x 0.8 mm	Dimension (flat blade connector)	6.3 x 0.8 mm
Identification colour	red	Insulation	Available
Material/plastic	PVC	Plastic collar diameter (D)	4 mm
Plastic collar length (b)	10 mm	Plug-in density (d3)	0.8 mm
Plug-in width (d2)	6.3 mm		

Classifications

ETIM 6.0	EC0005 16	ETIM 7.0	EC0005 16
ECLASS 9.0	27-44-03-92	ECLASS 9.1	27-40-02-90
ECLASS 10.0	27-44-03-92	ECLASS 11.0	27-44-03-92

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	EPLAN
------------------	-----------------------

Data sheet

LIF 1,5F638 R

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

