



CIRCUIT BREAKER 230V 6KA, 1+N-POLE, B, 32A

Similar to image

Technical data:

mounting position		any
Height	mm	90
Width	mm	72
Depth	mm	76
Mounting depth	mm	70
Current / for AC / rated value	A	32
Tripping characteristic class		B
Supply voltage		
• for AC / rated value	V	230
• with single-phase operation / with AC / rated value	V	230
Supply voltage frequency / rated value	Hz	50
Operating voltage		
• minimum	V	24
• with single-phase operation / with AC / maximum	V	250
• for DC / rated value / maximum	V	60
Number of poles		2
Number of poles /note		1P+N
Switching capacity current		

<ul style="list-style-type: none"> • in accordance with IEC 60947-2 / rated value • acc. to EN 60898 / rated value 	kA	6
	kA	6
Active power loss / at rated value current / with AC / in warm operating state / per pole	W	2.4
Number of pitch units for width		2
Product feature / sealable		Yes
Protection class IP		IP20, with connected conductors
Degree of pollution		2
Influence of the surrounding temperature		Periodically +55°C, max. 95% humidity
Ambient temperature	°C	-25 ... +45
Ambient temperature / during storage	°C	-40 ... +75
Mechanical operating cycles as operating time / typical		20,000
Product equipment / touch-protection		Yes
type of voltage		AC/DC
Insulation voltage <ul style="list-style-type: none"> • with single-phase operation / with AC / rated value 	V	250
Conductor cross-section that can be connected <ul style="list-style-type: none"> • solid • multibrin • finely stranded • with wire end processing 	mm ²	0.75 ... 35
	mm ²	0.75 ... 35
	mm ²	0.75 ... 25
Tightening torque <ul style="list-style-type: none"> • with screw-type terminals 	N·m	2.5 ... 3
Product feature <ul style="list-style-type: none"> • [not supplied - silicon-free] • halogen-free 		Yes
		Yes
Number of test cycles / for environmental testing / in accordance with IEC 60068-2-30		6
Item designation / according to DIN EN 61346-2		F
Device tag / according to DIN EN 81346-2		F

Certificates/approvals:

General Product Approval

Declaration of Conformity



[other](#)



other

[other](#)

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/maill>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SL6532-6/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6532-6

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Feb 18, 2013