

WB SI SL 0.4X2.5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration



If you demand effective and exact work, it is essential to use the precise torque. This also guarantees high repetition accuracy.

This is the perfect job for the new Weidmüller torque screwdriver with the ergonomic grip and the unique interchangeable bit system.

- Compact and especially light design
- Torque set with special tool (supplied); an unintended, incorrect setting is ruled out.
- Ergonomic handle sizes matched to the torque range.
- Tools subjected to routine testing and provided with an ID number; 100% quality control with verification and product reference.
- Clicking sound upon reaching the set torque, clearly audible and noticeable, no unnecessary tightening.
- Interchangeable blades made from high-quality wear-resistant tool steel.
- All tools fulfil the accuracy requirements of: EN ISO 6798, BS EN 26789, ASME B107.14M
- Trigger accuracy +/- 6% of the set scale value.

General ordering data

Version	Screwdriver insert
Order No.	2433160000
Type	WB SI SL 0.4X2.5
GTIN (EAN)	4050118443639
Qty.	1 pc(s).

WB SI SL 0.4X2.5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	7 mm	Depth (inches)	0.276 inch
Height	75 mm	Height (inches)	2.953 inch
Net weight	19 g	Width	7 mm
Width (inches)	0.276 inch		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	VDE-insulated interchangeable bit for slotted screws, size 0.4 x 2.5
------------------------	--

Screwing tools

Blade thickness (A)	0.4 mm	Blade width (B)	2.5 mm
Form	Slotted	Torque setting, max.	0.4 Nm

Classifications

ETIM 6.0	EC002116	ETIM 7.0	EC002116
ECLASS 9.1	21-04-04-90	ECLASS 10.0	21-04-04-90
ECLASS 11.0	21-04-42-04		

Downloads

Approval/Certificate/Document of Conformity	Manufacturer's Declaration - Slim Bits
---	--