



CIRCUIT BREAKER T55 230/400V, 6KA,
1-POLE, C, 25A

General technical data:		
type of voltage		AC/DC
Mounting depth	mm	55
Current / for AC / rated value	A	25
Tripping characteristic class		C
Supply voltage / for AC / rated value	V	400
Switching capacity current		
• in accordance with IEC 60947-2 / rated value	kA	10
• acc. to EN 60898 / rated value	kA	6
Number of pitch units for width		1
Degree of pollution		3
Overvoltage class		3

Certificates/approvals:

General Product Approval**Declaration of Conformity**

CSA



GOST



KETI



VDE



EG-Konf.

Test Certificates**Shipping Approval****other**[Special Test Certificate](#)[Type Test Certificates/Test Report](#)

LRS

[other](#)[Environmental Confirmations](#)**Further information:****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<http://www.siemens.com/lowvoltage/mall>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<http://support.automation.siemens.com/WW/view/en/5SX2125-7/all>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SX2125-7**CAX-Online-Generator**<http://www.siemens.com/cax>

last change:

Sep 24, 2012