



SIPLUS ET 200SP, BASEUNIT BU15-P16+A10+2B, BU-TYPE A0, -40 ... +70 DEGREES C WITH CONFORMAL COATING BASED ON 6ES7193-6BP20-0BA0 . PUSH-IN TERMINALS, WITH 10 AUX-TERMINALS, BRIDGED TO LEFT BU WXH: 15MMX141MM

Figure similar

Product type designation	
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Current carrying capacity	
up to 60 °C, max.	10 A
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	707 V DC
Extended ambient conditions	
<ul style="list-style-type: none"> relative to ambient temperature-atmospheric pressure-installation altitude 	Tmin ... Tmax at 1080 hPa ... 795 hPa (-1000 m ... +2000 m) // Tmin ... (Tmax - 10K) at 795 hPa ... 658 hPa (+2000 m ... +3500 m) // Tmin ... (Tmax - 20K) at 658 hPa ... 540 hPa (+3500 m ... +5000 m)
Relative humidity	
— With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
— against biologically active substances / conformity with EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna). The supplied connector covers must remain on the unused interfaces during operation!

— against chemically active substances /
conformity with EN 60721-3-3

Yes; Class 3C4 (RH < 75%) incl. salt spray according to EN 60068-2-52 (degree of severity 3). The supplied connector covers must remain on the unused interfaces during operation!

— against mechanically active substances /
conformity with EN 60721-3-3

Yes; Class 3S4 incl. sand, dust. The supplied connector covers must remain on the unused interfaces during operation!

Dimensions

Width	15 mm
Height	141 mm

Weights

Weight, approx.	50 g
-----------------	------

last modified: 10.06.2015